SAFETY DATA SHEET

Product : **WAY-PURE 68 - US**

Code : NC01264 Version : 2.3 Revision : 05-30-2022

1. Identification

Product identifier **WAY-PURE 68 - US**

Other means of identification

Product code NC01264

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CONDAT CORPORATION

Address 250 South Industrial
Saline, MI 48176
United States

Telephone Tel: +1 734-944-4994

Website www.condatcorp.com

E-mail arp-cco@condat.fr

Contact person ARP Dpt.

Emergency phone number Emergency Telephone Number:
24H/24H [US/Canada] : +1 734-944-4994
24H/24H [Mexico] : +52 55 41696225
Access code: 333637

2. Hazard(s) identification

Classification according to the OSHA 29 CFR 1910.1200 (HCS 2012) and the Canadian Hazardous Products Regulations (WHMIS 2015)

Physical hazards Not classified.

Health hazards Aspiration hazard Category 1

OSHA/HPR defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

The manufacturer lists no ingredients as hazardous according to the OSHA 29 CFR 1910.1200 (HCS 2012) and the Canadian Hazardous Products Regulations (WHMIS 2015).

Composition comments Occupational Exposure Limits for constituents are listed in Section 8.

- Contains : Mineral oil
DMSO Extract < 3% according to IP 346 Method.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth thoroughly. Do not induce vomiting.

Most important symptoms/effects, acute and delayed Aspiration may cause pulmonary edema and pneumonitis. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Foam. Dry chemicals. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical See also section 10.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods In the event of fire and/or explosion do not breathe fumes.

General fire hazards Will burn if involved in a fire. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will sediment in water systems. Prevent entry intc waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Local authorities should be advised if significant spillages cannot be contained. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash hands after handling. Handle in accordance with good industrial hygiene and safety practice. Adequate ventilation should be provided so that exposure limits are not exceeded.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in closed original container in a dry place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	TWA	5 mg/m3	Inhalable fraction.

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191), as amended

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Additional components	Type	Value	Form
OIL MIST, MINERAL (CAS SEQ100910)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Additional components	Type	Value
OIL MIST, MINERAL (CAS SEQ100910)	15 minute	10 mg/m3
	8 hour	5 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile. Polyvinyl chloride (PVC).

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. In case of inadequate ventilation, use respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Yellow. to Amber.

Odor Oily.

Odor threshold Not available.

pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	> 329.0 °F (> 165.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	7.3 lb/gal
Solubility(ies)	
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Nitrogen compounds. Carbon oxides. Sulfur compounds.

11. Toxicological information

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Elevated temperatures or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.
Skin corrosion/irritation	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Mobility in general The product is immiscible with water and will sediment in water systems.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not discharge into drains, water courses or onto the ground. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (DISTILLATES (PETROLEUM) SEVERELY SOLVENT-REFINED HEAVY PARAFFINIC)

Transport hazard class(es)

Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	8, 146, 173, 335, IB3, T4, TP1, TP29
Packaging exceptions	155
Packaging non bulk	203
Packaging bulk	241

IATA

UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (DISTILLATES (PETROLEUM) SEVERELY SOLVENT-REFINED HEAVY PARAFFINIC)

Transport hazard class(es)

Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES (PETROLEUM) SEVERELY SOLVENT-REFINED HEAVY PARAFFINIC), MARINE POLLUTANT

Transport hazard class(es)

Class	9
Subsidiary risk	-
Packing group	III


Environmental hazards

Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

TGD

UN3082
9
III
Read safety instructions, SDS and emergency procedures before handling.
16, 99
DISTILLATES (PETROLEUM) SEVERELY SOLVENT-REFINED HEAVY PARAFFINIC

DOT; IATA; IMDG; TDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All the components of this product comply with the U.S. EPA TSCA inventory requirements.

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

OIL MIST, MINERAL (CAS SEQ100910)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

16. Other information, including date of preparation or last revision

Revision date	05-30-2022
Version #	2.3
Further information	According to the "HMIS implementation manual (third edition)", "each employer is responsible for determining the appropriate protective equipment that employees are to wear when handling chemicals in the workplace."
List of abbreviations	AICIS: Australian Inventory of Industrial Chemicals.

CONDAT CORPORATION cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. This document complements the technical sheets but does not replace them. The information contained herein is based on our knowledge of the concerned product on the date indicated. It is offered in good faith. Furthermore, the regulatory requirements referred to must not be considered as exhaustive. They do not exempt in any form the user from knowing and applying all regulations related to the possession and use of the product. The user takes as their sole responsibility the implementation of precautions relating to storage and their use of the product.